

Hunter®

## PRO-SPRAY®

Professional Grade Sprinkler Heads

RESIDENTIAL & COMMERCIAL IRRIGATION  
*Built on Innovation*



# RUGGED-BODIED AND BUILT-TO-LAST

---

Hunter Pro-Spray sprinkler heads are precision engineered to ensure long-lasting, reliable performance in residential applications.

Available in heights from shrub to 30 cm, Pro-Spray heads feature durable construction that is second to none, exclusive body cap design which does not leak even when loosened, and a reliable, easy to adjust two-piece ratchet. Pro-Sprays are compatible with Pro-Adjustable nozzles,

fixed-arc nozzles, and MP Rotators. All models also include a user-friendly pull-ring flush cap to keep debris and clogging to a minimum. The Hunter Pro-Spray sprinkler head is compatible with all industry standard female nozzles offering a high degree of flexibility.



**Shown here:** PRS40 shrub, Pro-Spray 5 cm, PRS30 and PRS40 10 cm, Pro-Spray 15 cm, and PRS30 and PRS40 30 cm sprays



The Pro-Spray line incorporates a heavy-duty ribbed body and durable cap engineered to withstand the harshest environments.

#### CO-MOLDED WIPER SEAL

This pressure-activated, multi-function wiper seal was designed to reduce flow-by. The zero flush seal operates at low pressures and allows more sprinkler heads on the same zone. The wiper seal's design protects the riser when operating, and keeps debris out of the seal when retracted, reducing riser stick-ups.



#### HEAVY-DUTY SPRING

The strongest retraction spring for positive retraction under any conditions.



#### PRO-SPRAY CHECK VALVE

Optional check valves eliminate leaks and puddles at the lower heads, protecting landscapes from damage and erosion while reducing water waste. Choose from the convenience of factory-installed check valves or the flexibility of field installation.

#### PRESSURE-REGULATED TO 2.1 BAR (30 PSI) & 2.8 BAR (40 PSI)

Hunter's pressure regulated pop-up sprays are calibrated for the needs of any installation. The PRS30 with the brown cap optimizes performance of your traditional sprays at 2.1 bar (30 PSI). The grey-capped 2.8 bar (PRS40) is designed for the efficient MP Rotator and is the only 40 PSI regulated pop-up on the market today.



#### BODY CAP WON'T LEAK UNDER HIGH PRESSURE

The Pro-Spray line incorporates a heavy-duty ribbed body and durable cap engineered to withstand the harshest environments, including the rigors of foot traffic and the abuses of heavy machinery. In addition, a multi-thread buttress design provides superior strength in cap-to-body gripping capacity helping the head to withstand high inlet surge pressures.



Competitor



Pro-Spray

# PRO-SPRAY® PROFESSIONAL GRADE SPRINKLER HEADS

## Pro-Spray

Ready for commercial or residential projects, the Pro-Spray is a rugged and reliable sprinkler for versatile applications. The contractor's choice for years, it was designed with the professional in mind.

### Features

- Application: Residential/commercial
- Models: Shrub, 5 cm, 7.5 cm, 10 cm, 15 cm, 30 cm
- Compatible with all female threaded nozzles
- No side inlet (NSI) version available in 15 cm and 30 cm
- Innovative directional flush plug design
- Warranty period: 5 years

### Pro-Spray Reclaimed

Pro-Spray models come with optional factory-installed purple reclaimed caps.



### Vandal Proof Cap

Specify a Vandal Proof Cap (VPC) on the PRS30 to ensure a secured assembly and deter any unwarranted tampering.



## PRS30

An in-stem 2.1 bar (30 PSI) regulator provides optimal pressure to reduce water waste. Other features include a factory-installed check valve and the most powerful retraction spring in its class.

### PRS30 Features

- Models: Shrub, 10 cm, 15 cm, 30 cm
- No side inlet (NSI) version available in 15 cm and 30 cm
- Innovative directional flush plug design
- Warranty period: 5 years

## PRS40

Calibrated at a consistent 2.8 bar (40 PSI), the PRS40 delivers optimal performance and water efficiency when combined with the revolutionary MP Rotator.

### PRS40 Features

- Models: Shrub, 10 cm, 15 cm, 30 cm
- Identification cap is grey for easy field ID
- Innovative directional flush plug design
- Drain check valve installed with up to 4.3 m of elevation
- 15 cm and 30 cm models come standard as no side inlet ensuring proper installation with Check Valve.
- Warranty period: 5 years



**Website** [hunterindustries.com.au](http://hunterindustries.com.au) | **Customer Support** +1 760-744-5240 | **Technical Service** +1 760-591-7383

Helping our customers succeed is what drives us. While our passion for innovation and engineering is built into everything we do, it is our commitment to exceptional support that we hope will keep you in the Hunter family of customers for years to come.

  
Gregory R. Hunter, President of Hunter Industries